

## ESP-134/WS - PA Wall Speaker

100V 4Ω new



These wall speakers impress by an extraordinarily flat design which is only achieved by applying the latest NEODYMIUM magnetic systems.

The ESP-130... speaker systems already provide a very pleasant and complete sound and yet, with a total depth of only 38 mm, they are of such a flat design, that they are just as unobtrusive on the wall as a flush-mount speaker.

PA wall speaker

- 100 V line technique via audio transformer with 3 W and 6 W power taps or 4 Ohm operation (20 W)
- 2-way system with neodymium bass-midrange speaker and dome tweeter
- White plastic cabinet with protective metal grille
- Slimline design for unobtrusive wall mounting

## Tekniset tiedot:

|                                |                              |
|--------------------------------|------------------------------|
| Active/passive                 | : passive                    |
| Transmission method            | : 100 V or low-impedance     |
| Total output power             | : -                          |
| Power rating (RMS)             | : 6/3 W (100 V) 20 W (4 Ohm) |
| Total power rating             | : -                          |
| Power rating (RMS)             | : 6/3 W                      |
| Impedance                      | : 4 Ohm                      |
| Frequency range                | : 80-18,000 Hz               |
| THD                            | : -                          |
| S/N ratio                      | : -                          |
| Input signal                   | : -                          |
| System                         | : 2-way                      |
| Full range speaker             | : -                          |
| Bass speaker                   | : -                          |
| Midrange speaker               | : -                          |
| Tweeter                        | : -                          |
| Number of speakers             | : 2                          |
| Speaker size                   | : 130                        |
| Sensitivity                    | : 91 dB/W/m                  |
| Max. rated SPL                 | : 104 dB                     |
| Beam angle                     | : H: 100°/V: 60°             |
| Radiation angle, horizontal    | : 100°                       |
| Radiation angle, vertical      | : 60°                        |
| Features                       | : -                          |
| Housing material               | : plastic                    |
| Colour                         | : white                      |
| Mounting device                | : attachment via screw       |
| Protected against ball rebound | : -                          |
| Protection class               | : -                          |
| Admiss. ambient temp.          | : 0-40 °C                    |
| Power supply                   | : -                          |
| Dimensions                     | : 185 x 275 x 38 mm          |
| Width                          | : 185 mm                     |
| Height                         | : 275 mm                     |
| Depth                          | : 38 mm                      |



|                                |                           |
|--------------------------------|---------------------------|
| Weight                         | : 1.25 kg                 |
| Inputs                         | : spring-loaded terminal  |
| Outputs                        | : -                       |
| Replacement voice coil         | : -                       |
| Other features                 | : -                       |
| Accessories                    | : -                       |
| Packing dimensions (W x H x L) | : 0.075 x 0.225 x 0.315 m |
| Gross weight                   | : 1.375 kg                |
| Net weight                     | : 1.255 kg                |