

IT-33 - Horn Speaker



Weatherproof horn speaker

- 100 V line technique
- IP54 tested
- White ABS housing (self-extinguishing, complies with standard UL 94V-0)
- Particularly high power capability in relation to its size
- Suitable for general indoor and outdoor applications
- Integrated high-pass filter for optimising the sound and stability

Tekniset tiedot:

Active/passive	: passive
Transmission method	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: 25 W
Power rating (RMS)	: 25/12.5/6.25 W
Impedance	: -
Frequency range	: 500-13,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: -
Full range speaker	: -
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: 1
Speaker size	: -
Sensitivity	: 107 dB/W/m
Max. rated SPL	: -
Radiation angle, horizontal	: 90°
Radiation angle, vertical	: 90°
Features	: integrated high-pass filter
Housing material	: ABS, UL 94V-0
Colour	: white
Mounting device	: mounting bracket
Protected against ball rebound	: -
Protection class	: IP54
Admiss. ambient temp.	: -20 °C to +50 °C
Power supply	: -
Dimensions	: 130 mm x 175 mm
Width	: 130 mm
Height	: -
Depth	: 175 mm
Weight	: 1.8 kg



Inputs	: -
Outputs	: -
Replacement voice coil	: -
Other features	: weatherproof
Accessories	: -