

NBB-75DFGX - BNC Chassis Jack



NEUTRIK UHD BNC panel jacks provide low return loss values at high frequencies, which typically occur in high-definition video signal transmissions. The machined brass body ensures a rugged and non-abrasive connection. Due to being recessed in the D series body (audio industry standard) they are additionally protected.

UHD BNC feed-through panel jack, 75 Ohm, earthed

- Gold-plated cage type contact, optimised for UHD signals like 4 K or 8 K
- High-quality PTFE insulation
- Body with antralooy coating
- BNC insert is earthed via body
- Earthed panel mounting
- D series
- Colour coding possible
- Compatible with customary BNC cable connectors

Tekniset tiedot:

Description	: panel jack
Type	: NEUTRIK BNC feed-through
Quantity	: 1
Features	: PTFE insulation, gold-plated contacts
Colour/colour coding	: black
Power rating	: -
Insulating resistance	: $\geq 5 \text{ GOhm}$
Dielectric strength	: 1.5 kV
Certification	: -
Pole number	: -
Cable inlet	: -
Suitable cable cross section	: -
Connection	: 2 x BNC, 75 Ω Ohm
Strain relief	: -
Cable bending protection	: -
Stereo	: -
Mono	: -
Switches	: -
Material	: metal
Central fixing	: -
Contact type	: -
No. of contacts	: -
Contact width	: -
Contact distance	: -
Admiss. ambient temp.	: -30-+85 °C
Dimensions	: -
Diameter	: -
Length	: -
Weight	: 29 g
Other features	: D series