

PA-1120RC - PA Desk Microphone



PA zone paging desktop microphone,
for connection to PA-1120 and PA-1240.

- Push-buttons for selecting speaker zones 1-5 and ALL-CALL function
- Start/pause function for 6 selectable announcements which are stored in the digital module PA-1120DMT
- Adjustable line input (RCA L/R) for connection of a signal source, e.g. CD player or tape deck
- LED indication for transmission mode
- Autom. chime via microphone announcement button
- Power supply via PA-1120, PA-1240
- RJ45 jacks for connection to additional PA-1120RC microphones with slave/priority switch
- Supplied with connection module for PA-1120 and PA-1240

Tekniset tiedot:

Description	: PA desktop microphone
Version	: -
Transmission method	: cable
Polar pattern	: -
System	: -
Carrier frequency range	: -
Transmitting power	: -
Power supply	: via PA-1120, PA-1240
Operating time	: -
Audio frequency range	: -
Nominal impedance	: -
Sensitivity	: -
S/N ratio	: -
Max. sound pressure	: -
Power supply	: -
Gooseneck length	: -
Housing material	: -
Admiss. ambient temp.	: 0-40 °C
Dimensions	: -
Weight	: 1.49 kg
Cable	: -
Connection	: RJ45 (master/slave) RCA L/R (line in)