

## **EMG-330P - Electret Gooseneck Microphone**



Miniature electret directional microphone with gooseneck

- Transformer-balanced
- Hypercardioid/lobar polar pattern
- Foam windshield
- 3-pole XLR plug
- With optional desktop microphone base DMS-1, especially suitable as PA desktop microphone

## Tekniset tiedot:

|                         |                            |
|-------------------------|----------------------------|
| Description             | : directional microphone   |
| Version                 | : -                        |
| Transmission method     | : cable                    |
| Polar pattern           | : hypercardioid/lobar      |
| System                  | : back electret            |
| Carrier frequency range | : -                        |
| Transmitting power      | : -                        |
| Power supply            | : -                        |
| Operating time          | : -                        |
| Audio frequency range   | : 50-18,000 Hz             |
| Nominal impedance       | : 250 Ohm                  |
| Sensitivity             | : 10 mV/Pa                 |
| S/N ratio               | : -                        |
| Max. sound pressure     | : 125 dB                   |
| Power supply            | : DC 9-48 V, phantom power |
| Gooseneck length        | : -                        |
| Housing material        | : -                        |
| Admiss. ambient temp.   | : 0-40 °C                  |
| Dimensions              | : ~ 19 mm x 330 mm         |
| Weight                  | : 120 g                    |
| Cable                   | : -                        |
| Connection              | : 3-pole XLR               |