

PA-4000RC - PA Desk Microphone



PA 4-zone paging desktop microphone,
for connection to PA-40120 and PA-6040MPX.

- Selection buttons for 4 zones, for activating one or several zones
- ALL CALL button for activating all of the 4 zones
- Autom. chime via microphone announcement button (talk)
- LED status indication for the zone buttons (busy, emergency), power, mic fault, signal and talk
- Built-in gooseneck electret microphone
- Adjustable microphone sensitivity
- Chime can be activated or deactivated as required
- 24 V power supply via PA-40120 or PA-6040MPX
- Two RJ45 jacks for connection to PA-40120, PA-6040MPX or optional power supply and additional microphones PA-4000RC
- Supplied with connection module for PA-40120 and PA-6040MPX
- Up to 32 x PA-4000RC can be connected to PA-40120 or PA-6040MPX via bus
- Supplied with 3 m connection cable (Cat. 5e)

Tekniset tiedot:

Description	: PA desktop microphone
Version	: -
Transmission method	: cable
Polar pattern	: -
System	: -
Carrier frequency range	: -
Transmitting power	: -
Power supply	: via PA-40120, PA-6040MPX or optional 24 V power supply
Operating time	: -
Audio frequency range	: -
Nominal impedance	: -
Sensitivity	: -
S/N ratio	: -
Max. sound pressure	: -
Power supply	: -
Gooseneck length	: -
Housing material	: -
Admiss. ambient temp.	: 0-40 °C
Dimensions	: -
Weight	: 0.9 kg
Cable	: Cat. 5e, 3 m
Connection	: 2 x RJ45