

## ESP-50AB/WS - PA Wall Speaker



PA A/B wall speaker,  
with EN 54-24 certification for evacuation systems with A/B speaker distribution according to EN 60849 and DIN VDE 0833-4.

- 100 V line technique
- 2 separate full range speakers (10 cm), each with its own transformer 6/3/1.5 W
- Connection via 2 spring-loaded terminals inside the cabinet
- Wooden cabinet with protective metal grille
- Easy wall mounting via supplied metal bracket and mounting accessories
- Ball-proof according to DIN 18032, Part 3

## Tekniset tiedot:

|                                |                     |
|--------------------------------|---------------------|
| Active/passive                 | : passive           |
| Transmission method            | : 100 V             |
| Total output power             | : -                 |
| Power rating (RMS)             | : -                 |
| Total power rating             | : -                 |
| Power rating (RMS)             | : 2 x 6/3/1.5 W     |
| Impedance                      | : -                 |
| Frequency range                | : 120-20,000 Hz     |
| THD                            | : -                 |
| S/N ratio                      | : -                 |
| Input signal                   | : -                 |
| System                         | : -                 |
| Full range speaker             | : -                 |
| Bass speaker                   | : -                 |
| Midrange speaker               | : -                 |
| Tweeter                        | : -                 |
| Number of speakers             | : 2                 |
| Speaker size                   | : 10 cm             |
| Sensitivity                    | : 92 dB/W/m         |
| Max. rated SPL                 | : 99 dB             |
| Radiation angle, horizontal    | : -                 |
| Radiation angle, vertical      | : -                 |
| Features                       | : -                 |
| Housing material               | : wood              |
| Colour                         | : white             |
| Mounting device                | : metal bracket     |
| Protected against ball rebound | : yes               |
| Protection class               | : -                 |
| Admiss. ambient temp.          | : -10 °C to +50 °C  |
| Power supply                   | : -                 |
| Dimensions                     | : 265 x 165 x 90 mm |
| Width                          | : 265 mm            |
| Height                         | : 165 mm            |
| Depth                          | : 90 mm             |
| Weight                         | : 1.9 kg            |



|                        |     |
|------------------------|-----|
| Inputs                 | : - |
| Outputs                | : - |
| Replacement voice coil | : - |
| Other features         | : - |
| Accessories            | : - |