

## ESP-62/WS - PA Wall Speaker



**PA wall speaker**, with EN 54-24 certification.

- 100 V line technique via audio transformer with 3 power taps
- Full range speaker with a high-quality sound and a clear voice reproduction
- Plastic cabinet of a special design (open rear panel) with protective metal grille
- Symmetrical design allows for horizontal and vertical mounting
- Supplied with mounting screws and screw head covers
- Ball-proof according to DIN 18032, Part 3

## Tekniset tiedot:

Active/passive	: passive
Transmission method	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: -
Power rating (RMS)	: 6/3/1.5 W
Impedance	: -
Frequency range	: 100-19,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: -
Full range speaker	: -
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: -
Speaker size	: 130 mm
Sensitivity	: 93 dB/W/m
Max. rated SPL	: 101 dB
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: plastic
Colour	: white
Mounting device	: -
Protected against ball rebound	: yes
Protection class	: -
Admiss. ambient temp.	: -10 °C to +50 °C
Power supply	: -
Dimensions	: 240 x 330 x 85 mm
Width	: 240 mm
Height	: 330 mm
Depth	: 85 mm
Weight	: 1.2 kg



Inputs	: -
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -