

## RL-1ENABDS - Wall Speaker



PA A/B sound projector for wall mounting,  
with EN 54-24 certification for evacuation systems with A/B speaker distribution according to EN 60849.

- 100 V line technique
- 13 cm full range speaker with dual voice coil
- 2 x 100 V transformer with power taps on the cable 6/3/1.5 W
- Connection via 2 x 4-core cable (length: 1.5 m)
- Metal housing with front protective grille
- Supplied with pan/tilt bracket and mounting accessories

## Tekniset tiedot:

|                                |                          |
|--------------------------------|--------------------------|
| Active/passive                 | : passive                |
| Transmission method            | : 100 V                  |
| Total output power             | : -                      |
| Power rating (RMS)             | : -                      |
| Total power rating             | : -                      |
| Power rating (RMS)             | : 2 x 6/3/1.5 W          |
| Impedance                      | : -                      |
| Frequency range                | : 80-20,000 Hz           |
| THD                            | : -                      |
| S/N ratio                      | : -                      |
| Input signal                   | : -                      |
| System                         | : -                      |
| Full range speaker             | : 13 cm, dual voice coil |
| Bass speaker                   | : -                      |
| Midrange speaker               | : -                      |
| Tweeter                        | : -                      |
| Number of speakers             | : -                      |
| Speaker size                   | : 13 cm                  |
| Sensitivity                    | : 93 dB/W/m              |
| Max. rated SPL                 | : 101 dB                 |
| Radiation angle, horizontal    | : 130°                   |
| Radiation angle, vertical      | : 130°                   |
| Features                       | : -                      |
| Housing material               | : aluminium              |
| Colour                         | : white                  |
| Mounting device                | : bracket                |
| Protected against ball rebound | : -                      |
| Protection class               | : -                      |
| Admiss. ambient temp.          | : 0-40 °C                |
| Power supply                   | : -                      |
| Dimensions                     | : 144 mm x 210 mm        |
| Width                          | : 144 mm                 |
| Height                         | : -                      |
| Depth                          | : 210 mm                 |
| Weight                         | : 2.3 kg                 |



|                        |     |
|------------------------|-----|
| Inputs                 | : - |
| Outputs                | : - |
| Replacement voice coil | : - |
| Other features         | : - |
| Accessories            | : - |