

## CDMX-3 - DMX Cable 100m

100 m



Control lead,  
for transmitting digital DMX512 signals or AES/EBU signals.

- 100 m reel
- 2 x 0.22 mm<sup>2</sup>
- Metre marking
- Double shielding
- Outside diameter: Ø 4.5 mm
- High tensile strength
- Impedance level: 110 Ohm
- Very low capacitance: 57 pF/m

## Tekniset tiedot:

|                        |                            |
|------------------------|----------------------------|
| Intended use           | : DMX                      |
| Connectors             | : -                        |
| Cable specification    | : -                        |
| Length                 | : 100 m                    |
| Colour                 | : black                    |
| Cable diameter         | : $\approx$ 4.5 mm         |
| Metre marking          | : yes                      |
| Minimum bending radius | : -                        |
| Shielding              | : common, double           |
| Shielding value        | : -                        |
| Impedance              | : 110 Ohm                  |
| Attenuation            | : -                        |
| Capacitance            | : 57 pF/m                  |
| Power rating           | : -                        |
| Rated current          | : -                        |
| Internal conductor     | : 2 x 0.22 mm <sup>2</sup> |
| No. of cores           | : 2                        |
| Material               | : copper                   |
| Packaging              | : reel                     |
| Weight                 | : 3.28 kg                  |
| Position               | : -                        |
| Special feature        | : -                        |
| Other features         | : suitable for digital use |