

# PSL-12/12 - Built-in Power Supply



**LED switch-mode power supply, DC 12 V, for indoors.**

- Especially for LED installations
- 12 W
- Low-noise according to EMC standard EN 61000-3-2 class A
- Protected against short circuit, overload and overvoltage
- Connection via bare cable ends
- Plastic housing with mounting flange

## Tekniset tiedot:

|                             |                                |
|-----------------------------|--------------------------------|
| Category                    | : LED switch-mode power supply |
| Input voltage               | : $\approx$ 230 V/50 Hz        |
| Output voltage              | : DC 12 V                      |
| Charging/output current     | : 1 A                          |
| Charging time               | : -                            |
| Trickle charge              | : -                            |
| Polarity selection          | : -                            |
| Switchable output voltage   | : -                            |
| Reactivation                | : -                            |
| Connections                 | : -                            |
| Cable length                | : -                            |
| Short-circuit protection    | : yes                          |
| Overload protection         | : yes                          |
| Overheat protection         | : -                            |
| Reverse polarity protection | : -                            |
| Detection of faulty battery | : -                            |
| Protective class            | : -                            |
| Admiss. ambient temp.       | : -20-+50 °C                   |
| Dimensions                  | : 77 x 40 x 29 mm              |
| Weight                      | : 79 g                         |
| Position                    | : A                            |
| Other features              | : -                            |