

## HSE-152/SK - Headworn Microphone



### Ultra-light headband microphone

The reliable HSE-150 is now also available with cardioid polar pattern. Thus, the extensive list of features of the HSE-150 is now completed by a further important detail: excellent feedback rejection. This microphone also features a high-quality back electret cartridge which provides an optimum sound. The extra lightweight and almost invisible ergonomic headband makes the HSE-152 a perfect tool for every vocal artist.

- Wide transmission range
- Excellent feedback rejection
- Very comfortable to wear
- Stable positioning
- Turning cartridge arm of adjustable length
- Drip ring (protects cartridge from moisture)
- Compatible with all pocket transmitters TXS-...HSE with 3-pole mini XLR connection
- External power supply, e.g. via phantom power supply adapter EMA-1, EMA-2, EMA-40 or EMA-300P
- Microphone windshield

### Ultra-light headband microphone

- Cardioid polar pattern
- High-quality back electret cartridge
- 3-pole mini XLR connection
- Excellent feedback rejection
- Turning cartridge arm of adjustable length
- Drip ring (protects cartridge from moisture)
- Compatible with all pocket transmitters TXS-...HSE with 3-pole mini XLR connection
- External power supply, e.g. via phantom power supply adapter EMA-1 or EMA-300P



- Microphone windshield

## Tekniset tiedot:

|                         |                       |
|-------------------------|-----------------------|
| Description             | : headband microphone |
| Version                 | : -                   |
| Transmission method     | : cable               |
| Polar pattern           | : cardioid            |
| System                  | : back electret       |
| Carrier frequency range | : -                   |
| Transmitting power      | : -                   |
| Power supply            | : -                   |
| Operating time          | : -                   |
| Audio frequency range   | : 20-20,000 Hz        |
| Nominal impedance       | : 1.5 kOhm            |
| Sensitivity             | : 1.8 mV/Pa           |
| S/N ratio               | : -                   |
| Max. sound pressure     | : 130 dB              |
| Power supply            | : DC 1.5-9 V          |
| Gooseneck length        | : -                   |
| Housing material        | : -                   |
| Admiss. ambient temp.   | : 0-40 °C             |
| Dimensions              | : -                   |
| Weight                  | : 7 g                 |
| Cable                   | : -                   |
| Connection              | : 3-pole mini XLR     |