



SP-167C - Car Woofer



Car hi-fi bass-midrange speaker, 50 W, 4 Ohm

- 16 cm (6½") bass-midrange speaker
- Coated cone
- Also suitable as a bass addition for free air applications
- Protruding lower pole plate for a long excursion

Tekniset tiedot:

| | |
|---|-----------------------|
| Impedance (Z) | : 4 Ohm |
| Transmission method | : - |
| Frequency range | : f3-5,500 Hz |
| Resonant frequency (fs) | : 49 Hz |
| Rec. crossov. frequ. (fmax.) (12 dB/oct.) | : 3,000 Hz |
| Power rating (RMS) | : 50 W |
| Peak music power output (MAX) | : 100 W |
| Sensitivity | : 91 dB/W/m |
| Max. rated SPL | : - |
| Max. voltage | : - |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Suspension compl. (Cms) | : 0.84 mm/N |
| Moving mass (Mms) | : 12 g |
| Mech. Q factor (Qms) | : 2.89 |
| Electr. Q factor (Qes) | : 0.45 |
| Total Q factor (Qts) | : 0.39 |
| Equivalent volume (Vas) | : 22 l |
| DC resistance (Re) | : 3.7 Ohm |
| Force factor (BxL) | : 5.60 Tm |
| Voice coil induct. (Le) | : 0.2 mH |
| Voice coil diameter | : 25 mm |
| Voice coil former | : aluminium |
| Linear excursion (X _{MAX}) | : ± 4 mm |
| Eff. cone area (Sd) | : 137 cm ² |
| Magnet weight | : 570 g |
| Magnet diameter | : Å~ 100 mm |
| Mounting cutout | : Å~ 148 mm |
| Mounting depth | : 80 mm |
| Mounting hole diameter | : - |
| Hole spacing X-axis | : - |
| Hole spacing Y-axis | : - |
| Dimensions | : Å~ 170Å mm x 77 mm |
| Outside diameter | : Å~ 170 mm |
| Width | : Å~ 170 mm |



| | |
|-----------------------|-----------|
| Height | : - |
| Depth | : 77 mm |
| Protective class | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Weight | : 1.22 kg |
| Packing unit | : - |
| Type of speaker | : 6.5" |