



## HT-958PA/SW - Horn Speaker



**HT-958PA/SW**



Ring radiator tweeter, 30 W, 8 Ohm

- For PA and hi-fi
- High efficiency
- Very wide bandwidth radiation with an excellent linearity

## Tekniset tiedot:

Impedance (Z)	: 8 Ohm
Transmission method	: -
Frequency range	: fx-20 kHz
Resonant frequency (fs)	: 2.2 kHz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: 5 kHz
Power rating (RMS)	: 30 W
Peak music power output (MAX)	: 60 W
Sensitivity	: 101 dB/W/m
Max. rated SPL	: -
Max. voltage	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: -
Moving mass (Mms)	: -
Mech. Q factor (Qms)	: -
Electr. Q factor (Qes)	: -
Total Q factor (Qts)	: -
Equivalent volume (Vas)	: -
DC resistance (Re)	: -
Force factor (BxL)	: -
Voice coil induct. (Le)	: -
Voice coil diameter	: $\varnothing \sim 25.4$ mm
Voice coil former	: -
Linear excursion (X <sub>MAX</sub> )	: -
Eff. cone area (Sd)	: -
Magnet weight	: -
Magnet diameter	: $\varnothing \sim 72$ mm
Mounting cutout	: $\varnothing \sim 75$ mm
Mounting depth	: 45 mm
Mounting hole diameter	: -
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: $\varnothing \sim 97$ mm x 45 mm
Outside diameter	: $\varnothing \sim 97$ mm
Width	: $\varnothing \sim 97$ mm

Height	: -
Depth	: 45 mm
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 0.525 kg
Packing unit	: 1
Type of speaker	: -