

TXS-606HT/2 - Handheld Transmitter



Hand-held microphone with integrated multifrequency transmitter, with UHF PLL technology.

- Dynamic microphone cartridge, cardioid polar pattern
- 800 selectable UHF frequencies (672.000-691.975 MHz), can be synchronised with receivers TXS-606, TXS-626, TXS-646 or TXS-686 via ACT function
- Adjustable sensitivity
- Switchable transmitting power (high: 25 mW/low: 2.5 mW)
- LCD for indicating group/channel, audio level and battery status
- Power supply via 2 x 1.5 V battery AA size (not supplied)

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!

SOUNDCHECK 04/2012

"The TXS-646 can receive four wireless channels at the same time - the hand-held transmitter provides a warm and powerful sound and stands its ground among the instruments ... the earband microphones allow for unobtrusive miking with both a low susceptibility to acoustic feedback and an excellent speech intelligibility ... the quad wireless system from IMG Stage Line provides a reliable operation at all times, is easy to use and impresses by a crisp sound."

+ Clear sound

+ Very good price-performance ratio

+ Future-proof frequency range

(Test setup consisted of TXA-646 with TXS-606HT, TXS-606LT and HSE-70A/SK)

Tekniset tiedot:

| | |
|-------------------------|------------------------------------|
| Description | : hand-held microphone transmitter |
| Version | : - |
| Transmission method | : wireless |
| Polar pattern | : cardioid |
| System | : dynamic |
| Carrier frequency range | : 672.000-691.975 MHz |
| Transmitting power | : 25 mW/2.5 mW |
| Power supply | : 2 x 1.5 V batt. AA size |
| Operating time | : ? 8 h |
| Audio frequency range | : 30-18,000 Hz |
| Nominal impedance | : - |
| Sensitivity | : - |
| S/N ratio | : - |
| Max. sound pressure | : - |
| Power supply | : - |
| Gooseneck length | : - |
| Housing material | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Dimensions | : ~ 51 mm x 265 mm |
| Weight | : 312 g |
| Cable | : - |
| Connection | : - |