

TXS-812SET - Wireless Microphone



Wireless 2-channel microphone system

- 2 microphone transmitters, 1 receiver, 1 plug-in power supply
- Two-channel UHF version (non-diversity) with channel mixing function which can additionally be selected
- Volume and squelch controls for each channel
- Each channel with LEDs for indicating RF signal and audio signal

Licence-free in the EU.

Tekniset tiedot:

General information

	: -
Description	: wireless microphone system
Carrier frequency range	: 863.80 MHz , 864.20 MHz
Audio frequency range	: 40-15,000 Hz
Channels	: 2
THD	: < 0.5%
Dynamic range	: ? 90 dB
RF S/N ratio	: ? 80 dB
Operating time	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: -
Total weight	: -
Connections	: -

Specifications transmitter

	: -
Transmitting power	: < 10 mW
Operating range	: approx. 30 m
Power supply transmitter	: 2 x 1.5 V batt. AA size (not supplied)

Width transmitter	: 52 mm
Height transmitter	: 52 mm
Depth transmitter	: 260 mm
Weight transmitter	: 240 g
Connections transmitter	: -

Specifications receiver

	: -
Audio signal receiver	: 0-200 mV/10 kOhm (jack)0-400 mV/10 kOhm (XLR, bal.)
Power supply receiver	: via encl. plug-in power supply
Width receiver	: 210 mm
Height receiver	: 46 mm
Depth receiver	: 190 mm
Weight receiver	: 560 g
Connections receiver	: 2 x XLR, bal.1 x 6.3 mm jack, unbal.