

## TXS-865HSE - Microphone Transmitter



**The improvement of the transmission quality and maximising the operating range ensure reliability and provide flexibility!**

These features have been realised by an innovative circuit design and a switchable transmitting power. A high-quality wireless audio transmission of up to 300 m in a free field outdoors is thus possible without any problems!

Rapid transmission: due to REMOSET, the frequency of a corresponding hand-held transmitter or pocket transmitter can easily be set up via the receiver. It is possible to remotely set the desired transmission channel at the transmitter via radio signal, no visual contact required. This can even be done during a live performance! An intelligent carrier analysis method provides user support by only allowing transmission channels on which no other transmitter is active.

**UHF PLL pocket transmitter,**  
with REMOSET technology.

- Suitable for the combination with headband microphone or earband microphone with 3-pole mini XLR connector
- 124 selectable channels in 6 channel groups (506-542 MHz)
- Adjustable sensitivity (12 dB to -18 dB)
- Selectable attenuation (0 dB/-6 dB/-20 dB)
- Lock function
- Backlit LCD for indicating channel and battery status
- Transmitting power: 10 mW (EIRP)
- Power supply via 2 x 1.5 V battery AA size (not supplied)

**There are restrictions or requirements within the EU!**

**Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!**

## Tekniset tiedot:

### General information

	: -
Description	: pocket transmitter
Carrier frequency range	: 506-542 MHz
Audio frequency range	: 40-18,000 Hz
Channels	: 1
THD	: -
Dynamic range	: -
RF S/N ratio	: -
Operating time	: ? 25 h
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: -
Total weight	: -
Connections	: -

### Specifications transmitter

	: -
Transmitting power	: 10 mW
Operating range	: -
Power supply transmitter	: 2 x batt. AA size,alkaline

Width transmitter	: 68 mm
Height transmitter	: 172 mm
Depth transmitter	: 21 mm
Weight transmitter	: 77 g
Connections transmitter	: 1 x 3-pole mini XLR
Specifications receiver	: -
Audio signal receiver	: -
Power supply receiver	: -
Width receiver	: -
Height receiver	: -
Depth receiver	: -
Weight receiver	: -
Connections receiver	: -