

## DRM-884RC - Paging Microphone



PA zone paging microphone,  
for audio matrix router DRM-884.

- LCD for selected zones (1-32), volume and ID number
- LED indication for signal status
- Volume control (assignable for each zone)
- Zone selector control
- Momentary push-to-talk button
- Plug-in electret gooseneck microphone (NEUTRIK 3-pole XLR jack)
- USB port for loading sound files containing chimes
- Power supply via audio matrix router DRM-884
- Connection to DRM-884 via RJ45 jack and Cat. 5e network cable (supplied w/o cable), cable length up to 100 m

## Tekniset tiedot:

|                         |                             |
|-------------------------|-----------------------------|
| Description             | : PA zone paging microphone |
| Version                 | : -                         |
| Transmission method     | : cable                     |
| Polar pattern           | : -                         |
| System                  | : -                         |
| Carrier frequency range | : -                         |
| Transmitting power      | : -                         |
| Power supply            | : -                         |
| Operating time          | : -                         |
| Audio frequency range   | : -                         |
| Nominal impedance       | : -                         |
| Sensitivity             | : -                         |
| S/N ratio               | : -                         |
| Max. sound pressure     | : -                         |
| Power supply            | : -                         |
| Gooseneck length        | : 310 mm                    |
| Housing material        | : -                         |
| Admiss. ambient temp.   | : 0-40 °C                   |
| Dimensions              | : 176 x 70 x 162 mm         |
| Weight                  | : 811 g                     |
| Cable                   | : -                         |
| Connection              | : RJ45, micro USB           |