

## DMG-700 - Dynamic Gooseneck Mike



Dynamic gooseneck microphone

- Balanced connection
- Cardioid polar pattern
- 3-pole XLR connection
- Total length: 700 mm
- Supplied with microphone windshield WS-40

## Tekniset tiedot:

|                         |                        |
|-------------------------|------------------------|
| Description             | : gooseneck microphone |
| Version                 | : -                    |
| Transmission method     | : cable                |
| Polar pattern           | : cardioid             |
| System                  | : dynamic              |
| Carrier frequency range | : -                    |
| Transmitting power      | : -                    |
| Power supply            | : -                    |
| Operating time          | : -                    |
| Audio frequency range   | : 80-16,000 Hz         |
| Nominal impedance       | : 500 Ohm              |
| Sensitivity             | : 1.4 mV/Pa            |
| S/N ratio               | : -                    |
| Max. sound pressure     | : -                    |
| Power supply            | : -                    |
| Gooseneck length        | : -                    |
| Housing material        | : -                    |
| Admiss. ambient temp.   | : 0-40 °C              |
| Dimensions              | : Å~ 30 mm x 700 mm    |
| Weight                  | : 232 g                |
| Cable                   | : -                    |
| Connection              | : 3-pole XLR           |