

## ATS-20R - Receiver



### 16-channel Digital Voice Transmission System, 863-865 MHz

- Suitable as a tour guide system and for any other application in which a certain voice source is to be distributed to one or more receivers
- High resistance to interference due to digital transmission
- High operating range
- Frequency range perfectly adapted to voice transmissions
- Parallel operation of up to 4 different channels possible without any interference
- Extra small and lightweight transmitters and receivers
- Licence-free in the EU

### 16-channel miniature receiver

- Supplied with matching clip-on earphone
- Switches off automatically after not receiving an input signal for 20 minutes (power-saving function)
- LCD for indicating channel, carrier signal, volume and battery status
- Autolock function
- Lanyard
- Power supply via integrated rech. lithium battery (3.7 V/600 mAh)
- Micro USB charging connection for ATS-12CB, ATS-35CB or USB charger, available at option
- Dimensions: 40 x 87 x 12 mm
- Weight: 37 g

**Licence-free in the EU.**

## Tekniset tiedot:

### General information

|                                |   |
|--------------------------------|---|
|                                | : -   |
| Description                    | : 16-channel digital miniature receiver           |
| Carrier frequency range        | : 863-865 MHz                                     |
| Audio frequency range          | : -   |
| Channels                       | : -   |
| THD                            | : -   |
| Dynamic range                  | : -   |
| RF S/N ratio                   | : -   |
| Operating time                 | : -   |
| Admiss. ambient temp.          | : 0-40 °C   |
| Power supply                   | : -   |
| Dimensions                     | : -   |
| Total weight                   | : -   |
| Connections                    | : -   |
| Specifications transmitter     | : -   |
| Transmitting power             | : -   |
| Operating range                | : -   |
| Power supply transmitter       | : -   |
| Width transmitter              | : -   |
| Height transmitter             | : -   |
| Depth transmitter              | : -   |
| Weight transmitter             | : -   |
| Connections transmitter        | : -   |
| <b>Specifications receiver</b> | : -   |
| Audio signal receiver          | : -   |
| Power supply receiver          | : integrated rech. lithium batt. (3.7 V/600 mAh)  |
| Width receiver                 | : 40 mm   |
| Height receiver                | : 87 mm   |
| Depth receiver                 | : 12 mm   |
| Weight receiver                | : 37 g  |
| Connections receiver           | : 3.5 mm jack (earphone), micro USB charging port |