

TXA-802SR - Receiver



Professional 16-channel Mono PLL Audio Transmission System, 863-865 MHz

- Compatible with portable amplifier systems of the TXA-800 and TXA-1020 series
- Can be combined with the TXA-800 and TXA-1020 series, but also suitable as a tour guide system and for any other application in which a certain audio source or voice source is to be distributed to one or more receivers
- Licence-free in the EU.

Professional 16-channel Mono PLL Audio Transmission System, 863-865 MHz, with Extensive Accessories

- Compatible with portable amplifier systems of the TXA-800 and TXA-1020 series
- Can be combined with the TXA-800 and TXA-1020 series, but also suitable as a tour guide system and for any other application in which a certain audio source or voice source is to be distributed to one or more receivers
- Can be combined with transmitters and receivers of the ATS-16 series
- Simultaneous operation of up to 4 transmitters with different frequencies (dep. on distance of transmitters, stationary RF sources of interference and other local conditions)
- Licence-free in the EU

2-channel multifrequency receiver, with UHF PLL technology.

- Matching the transmitters TXA-800HT, TXA-800HSE, TXA-802ST and ATS-12HT
- 2 x 16 selectable UHF frequencies (863.1-864.9 MHz) with diversity system
- Scan function for free channel
- Volume control
- LCD for indicating selected channel and carrier signal



- Balanced XLR output and 6.3 mm jack output
- 482 mm (19") rack installation of 2 devices is possible with supplied mounting brackets
- Power is provided via enclosed plug-in power supply
- Dimensions: 215 x 50 x 210 mm
- Weight: 1.2 kg

Licence-free in the EU.

Tekniset tiedot:

General information

| | |
|----------------------------|-------------------|
| | : - |
| Description | : receiver unit |
| Carrier frequency range | : 863.1-864.9 MHz |
| Audio frequency range | : - |
| Channels | : 2 |
| THD | : - |
| Dynamic range | : - |
| RF S/N ratio | : - |
| Operating time | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : - |
| Dimensions | : - |
| Total weight | : - |
| Connections | : - |
| Specifications transmitter | : - |
| Transmitting power | : - |
| Operating range | : - |
| Power supply transmitter | : - |
| Width transmitter | : - |
| Height transmitter | : - |
| Depth transmitter | : - |
| Weight transmitter | : - |
| Connections transmitter | : - |

Specifications receiver

| | |
|-----------------------|---|
| Audio signal receiver | : 30 mV (XLR), 730 mV (6.3 mm jack, high), 80 mV (6.3 mm jack, low) |
| Power supply receiver | : via encl. plug-in power supply |
| Width receiver | : 215 mm |
| Height receiver | : 50 mm |
| Depth receiver | : 210 mm |
| Weight receiver | : 1.2 kg |
| Connections receiver | : 1 x XLR, bal., 1 x 6.3 mm jack, unbal. |