

STA-400D - Digital Amplifier



The new generation of digital PA amplifiers from IMG STAGELINE impresses with a high power capability and high energy efficiency. Other features include a silent operation and a low weight which make this series suitable for both fixed installations and mobile applications. **Digital stereo PA amplifier**

- Class D concept with power amplifier modules from HYPEX
- 482 mm (19") rack installation, 1 RS, with supplied mounting brackets
- Silent operation due to temperature-controlled fans
- Lightweight design due to compact switch-mode power supply
- Energy-efficient concept due to high efficiency
- Powerful bass reproduction due to large buffer capacitors (high power reserves)
- 2 level controls
- Protected against short circuit and overtemperature
- LEDs for indicating power, overload (clip) and protect
- Super slimline design
- NEUTRIK SPEAKON connections

EVENT Rookie 01/2015

on the STA-400D and STA-800D

"Small and powerful surely applies to them. The two test units didn't really show any weakness. It should be noted that the minimum noise created by the two amplifiers is almost record-breaking ..."

Tekniset tiedot:

Peak output power	: 700 W
Power rating	: 540 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: 2 x 270 W
Power rating at 8 Ohm	: 2 x 180 W
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: -
Output impedance	: -
Channels	: 2
Zones	: -
Inputs	: 1 \hat{A} V/10 kOhm (XLR, bal.), 1 V/4.7 \hat{A} kOhm (RCA)
Attenuation factor	: -
Frequency range	: 20-20,000 \hat{A} Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: no
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: ? 110 dBA
Crosstalk attenuation	: -
THD	: < 0.02%
Mains voltage	: \sim 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 600 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 $^{\circ}$ C
Width	: 482 mm
Height	: 52 mm

Depth

: 277 mm



Stage Line®

Rack spaces, RS	: 1
Weight	: 3.5 kg
Connections	: 1 x 3-pole XLR L/R1 x RCA L/R1 x NEUTRIK SPEAKON L/R2 x pair of screw terminals