

## PA-948S - PA Amplifier



### Mono PA power amplifier

- 1 x 480 W
- Temperature-controlled fan, continuously adjustable
- Protected against overheating, overload and short circuit
- LED indication for clip, protect, overtemperature, output level and 100 V/70 V
- Feed-through output (link)
- Speaker outputs via screw terminals

## Tekniset tiedot:

Peak output power	: -
Power rating	: 480 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: -
Power rating at 8 Ohm	: -
Power rating at 16 Ohm	: -
Power rating at 100 V	: 1 x 480 W
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: -
Output impedance	: 70 V/10 Ohm, 100 V/20 Ohm
Channels	: 1
Zones	: -
Inputs	: 710 mV/10 kOhm, balanced
Attenuation factor	: -
Frequency range	: 80-16,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: ? 98 dBA
Crosstalk attenuation	: -
THD	: < 1%
Mains voltage	: ~ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 1,100 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 483 mm
Height	: 44 mm
Depth	: 255 mm



Rack spaces, RS	: 1
Weight	: 4 kg
Connections	: 1 x 6.3 mm/XLR combo (input), 1 x XLR (link), screw terminals (speakers)