

PA-6000RC - PA Desk Microphone



PA zone paging desktop microphone,
for connection to PA-6240, PA-6480 and PA-6600.

- Push-buttons for selecting speaker zones 1-6 and ALL-CALL function
- Start/pause function for 6 selectable announcements which are stored in the digital module PA-1120DMT
- Autom. chime via microphone announcement button
- Adjustable line input (RCA L/R) for connection of a signal source, e.g. CD player or tape deck
- LED indication for transmission mode
- Power supply via PA-6240, PA-6480, PA-6600
- RJ45 jack for connection to additional PA-6000RC microphones with slave/priority switch
- Supplied with connection module for PA-6240, PA-6480 and PA-6600

Tekniset tiedot:

| | |
|-------------------------|---|
| Description | : PA desktop microphone |
| Version | : - |
| Transmission method | : cable |
| Polar pattern | : - |
| System | : - |
| Carrier frequency range | : - |
| Transmitting power | : - |
| Power supply | : via PA-1120, PA-1240 |
| Operating time | : - |
| Audio frequency range | : - |
| Nominal impedance | : - |
| Sensitivity | : - |
| S/N ratio | : - |
| Max. sound pressure | : - |
| Power supply | : - |
| Gooseneck length | : - |
| Housing material | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Dimensions | : - |
| Weight | : 1.45 kg |
| Cable | : - |
| Connection | : RJ45 (master/slave) RCA L/R (line in) |