

NAC-3FX-W-TOP - Powercon inline jack

IP65



NEUTRIK POWERCON True1 TOP inline jack

- Complies with safety requirements of IEC 60320, VDE-certified
- For mains connection up to ? 250 V/16 A
- Connections for ground, phase and neutral conductor, connector can be connected under load
- Self-extinguishing according to UL 94V-0
- Protection classs IP65

Tekniset tiedot:

Description	: inline jack
Type	: NEUTRIK POWERCON TOP
Quantity	: 1
Features	: latching device
Colour/colour coding	: black
Power rating	: ∿Â 250Â V/16Â A
Insulating resistance	: ? 100 MOhm
Dielectric strength	: DC 4 kV/∿ 2.8 kV
Certification	: UL, VDE
Pole number	: 2+PE
Cable inlet	: 6-12 mm
Suitable cable cross section	: -
Connection	: -
Strain relief	: yes
Cable bending protection	: -
Stereo	: -
Mono	: -
Switches	: -
Material	: silver-plated bronze contacts, plastic
Central fixing	: -
Contact type	: -
No. of contacts	: -
Contact width	: -
Contact distance	: -
Admiss. ambient temp.	: -30-+80 °C
Dimensions	: Ã~ 26.5 mm x 77-80 mm
Diameter	: -
Length	: -
Weight	: 33 g
Other features	: -