

NAC3MX-W-TOP - Powercon inline plug



NEUTRIK POWERCON True1 TOP Connectors

- Complies with safety requirements of IEC 60320, VDE-certified
- For mains connection up to ? 250 V/16 A
- Connections for ground, phase and neutral conductor, connector can be connected under load
- Robust version with latching device and cable inlet with self-adjusting clamps (plug and inline jack only)
- Self-extinguishing according to UL 94V-0
- Protection classs IP65 (NAC3FX-W-TOP and NAC3MX-W-TOP)

NEUTRIK POWERCON True1 TOP plug

- Complies with safety requirements of IEC 60320, VDE-certified
- For mains connection up to ? 250 V/16 A
- Connections for ground, phase and neutral conductor, connector can be connected under load
- Robust version with latching device and cable inlet with self-adjusting clamps
- Self-extinguishing according to UL 94V-0
- Protection classs IP65

Tekniset tiedot:

| | |
|------------------------------|--|
| Description | : plug |
| Type | : NEUTRIK POWERCON TOP |
| Quantity | : 1 |
| Features | : latching device |
| Colour/colour coding | : black |
| Power rating | : ∿Â 250Â V/16Â A |
| Insulating resistance | : ? 100 MOhm |
| Dielectric strength | : DC 4 kV/∿ 2.8 kV |
| Certification | : UL, VDE |
| Pole number | : 2+PE |
| Cable inlet | : 6-12 mm |
| Suitable cable cross section | : - |
| Connection | : - |
| Strain relief | : yes |
| Cable bending protection | : - |
| Stereo | : - |
| Mono | : - |
| Switches | : - |
| Material | : silver-plated bronze contacts, plastic |
| Central fixing | : - |
| Contact type | : - |
| No. of contacts | : - |
| Contact width | : - |
| Contact distance | : - |
| Admiss. ambient temp. | : -30-+80 °C |
| Dimensions | : Ã~ 26.5 mm x 77-80 mm |
| Diameter | : - |
| Length | : - |
| Weight | : 32 g |
| Other features | : - |