

EDL-430/WS - PA Loudspeaker



Top-quality PA ball speaker,
with a perfect omnidirectional sound radiation.

- 100 V line technique
- High-performance full range speaker
- Extensive reflector design
- Great speech intelligibility
- White ABS housing
- 150 cm connection cable with canopy

Tekniset tiedot:

Active/passive	: passive
Transmission method	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: -
Power rating (RMS)	: 20/10/5 W
Impedance	: -
Frequency range	: 80-15,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: -
Full range speaker	: -
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: -
Speaker size	: -
Sensitivity	: 92 dB/W/m
Max. rated SPL	: -
Radiation angle, horizontal	: 360°
Radiation angle, vertical	: -
Features	: -
Housing material	: ABS
Colour	: white
Mounting device	: -
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: -20 °C to +50 °C
Power supply	: -
Dimensions	: ~ 250 mm
Width	: ~ 250 mm
Height	: -
Depth	: -
Weight	: 2.3 kg



Inputs	: -
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -