

## FGA-40HQ - Ground Insulator



**High-end ground isolator,**

for preventing signal interference and hum loops which may occur, e.g. when connecting the car radio to an amplifier.

- Gold-plated RCA jacks
- Input/output impedance: 12 kOhm
- Frequency range: 20-30,000 Hz
- THD: < 0.001%
- Transmission ratio: 1:1
- 42 x 29 x 96 mm, 110 g

## Tekniset tiedot:

|                       |                   |
|-----------------------|-------------------|
| Description           | : ground isolator |
| Frequency range       | : 20-30,000 Hz    |
| Control range         | : -               |
| Control frequencies   | : -               |
| Input signal          | : -               |
| Input sensitivity     | : -               |
| Input impedance       | : 12 kOhm         |
| Output signal         | : -               |
| Output impedance      | : 12 kOhm         |
| Gain                  | : -               |
| Phantom power         | : -               |
| Compression           | : -               |
| Gate ratio            | : -               |
| Crossover frequency   | : -               |
| High-pass filter      | : -               |
| Low cut               | : -               |
| Transmission ratio    | : 1:1             |
| S/N ratio             | : -               |
| Channel separation    | : -               |
| THD                   | : < 0.001%        |
| Admiss. ambient temp. | : 0-40 °C         |
| Power supply          | : -               |
| Dimensions            | : 42 x 29 x 96 mm |
| Weight                | : 105 g           |
| Inputs                | : 1 x RCA L/R     |
| Outputs               | : 1 x RCA L/R     |
| Other features        | : -               |