

FGA-102 - Line Isolator



Professional stereo line transformer,
for reducing signal interference and hum loops which may occur, e.g. when connecting PC sound cards to
hi-fi systems or mixers.

- Galvanically isolated inputs and outputs
- Gold-plated RCA connections (600 Ohm)
- Frequency range: 20-20,000 Hz
- Robust metal housing with very good shielding qualities, suitable for stage applications
- Dimensions: 125 x 55 x 75 mm
- Weight: 650 g

SOUNDCHECK 07/2007

on the FGA-102, FGA-202, LC-31, MC-31 and LSP-102:

“Every musician or sound engineer should have these little helpers in their toolbox. They impress by their unobtrusiveness. Both the robust metal housing and the functionality of these transformers allow to solve many problems on stage or in the studio at a reasonable price.”

tools4music 06/2009

on the LSP-102, LC-31, FGA-102, FGA-202, DIB-102

“Recommendable and fit for on-the-road applications. An attractively priced little audio aid, perfect for the
'ever accompanying' tool case.”

Tekniset tiedot:

Description	: transformer
Frequency range	: 20-20,000 Hz
Control range	: -
Control frequencies	: -
Input signal	: -
Input sensitivity	: -
Input impedance	: 600 Ohm
Output signal	: -
Output impedance	: -
Gain	: -
Phantom power	: -
Compression	: -
Gate ratio	: -
Crossover frequency	: -
High-pass filter	: -
Low cut	: -
Transmission ratio	: -
S/N ratio	: -
Channel separation	: -
THD	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: 125 x 55 x 75 mm
Weight	: 650 g
Inputs	: 1 x RCA L/R
Outputs	: 1 x RCA L/R
Other features	: -