

ETS-530TW/WS - PA Speaker Column



PA column speakers

- 100 V line technique or 8 Ohm operation
- 2-way version (with additional integrated tweeter for a clearly improved sound)
- Integrated crossover network
- 6-step power selector switch with 8 Ohm switching
- 2 x 6 mm threaded bushing
- Plastic cabinet and protective metal grille in black (SW) or white (WS)
- Supplied with mounting brackets
- Connection via spring-loaded speaker terminal

Tekniset tiedot:

| | |
|--------------------------------|--|
| Active/passive | : passive |
| Transmission method | : 100 V |
| Total output power | : - |
| Power rating (RMS) | : - |
| Total power rating | : 60 W |
| Power rating (RMS) | : 30/15/7.5/4/2 W (100 V) 30 W (8 Ohm) |
| Impedance | : 8 Ohm |
| Frequency range | : 85-20,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : - |
| System | : 2-way |
| Full range speaker | : - |
| Bass speaker | : - |
| Midrange speaker | : - |
| Tweeter | : - |
| Number of speakers | : 4+1 |
| Speaker size | : - |
| Sensitivity | : 89 dB/W/m |
| Max. rated SPL | : - |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Features | : - |
| Housing material | : plastic |
| Colour | : white |
| Mounting device | : mounting brackets |
| Protected against ball rebound | : - |
| Protection class | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : - |
| Dimensions | : 128 x 620 x 140 mm |
| Width | : 128 mm |
| Height | : 620 mm |
| Depth | : 140 mm |
| Weight | : 4.5 kg |



| | |
|------------------------|-----|
| Inputs | : - |
| Outputs | : - |
| Replacement voice coil | : - |
| Other features | : - |
| Accessories | : - |