

KU-516 - Horn Driver



Weatherproof horn driver

- Diecast version, IP66
- Protected against powerful water jets
- 3.5 cm (1 1/4") mounting flange

Tekniset tiedot:

Active/passive	: passive
Transmission method	: -
Total output power	: -
Power rating (RMS)	: -
Total power rating	: 75 W
Power rating (RMS)	: 50 W
Impedance	: 16 Ohm
Frequency range	: 160-6,500 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: -
Full range speaker	: -
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: 1
Speaker size	: -
Sensitivity	: 113 dB/W/m
Max. rated SPL	: -
Radiation angle, horizontal	: dep. on horn
Radiation angle, vertical	: dep. on horn
Features	: -
Housing material	: diecast
Colour	: dark grey
Mounting device	: 3.5 mm mounting flange
Protected against ball rebound	: -
Protection class	: IP66
Admiss. ambient temp.	: -20 °C to +50 °C
Power supply	: -
Dimensions	: 125 mm x 100 mm
Width	: 125 mm
Height	: -
Depth	: 100 mm
Weight	: 1.9 kg



Inputs	: -
Outputs	: -
Replacement voice coil	: KU-516/VC
Other features	: weatherproof
Accessories	: -