

## PA-1200 - PA Amplifier



4-zone mono PA mixing amplifier

- 1 x 120 W
- Silent operation due to fanless cooling concept
- Chime, continuous sound and wailing sound, automatic mute, chime can also be activated via external momentary push-button, 2-tone chime or 4-tone chime (selectable)
- Bass, treble and master controls, level display via LEDs
- 15 V phantom power for channels 2 and 3
- Insertions for various functions are available at option
- 482 mm (19") rack installation with mounting frame PA-1200RM, available at option
- Mains operation and 24 V emergency power operation

## Tekniset tiedot:

|  |   |
|--|---|
| Peak output power                        | : 170 W   |
| Power rating                             | : 120 W   |
| Power rating at 2 Ohm                    | : -   |
| Power rating at 4 Ohm                    | : -   |
| Power rating at 8 Ohm                    | : -   |
| Power rating at 16 Ohm                   | : -   |
| Power rating at 100 V                    | : -   |
| Power rating with 4 Ohm                  | : -   |
| bridged operation                        |   |
| Power rating with 8 Ohm                  | : -   |
| bridged operation                        |   |
| Output impedance                         | : -   |
| Channels                                 | : 5   |
| Zones                                    | : 4   |
| Inputs                                   | : 1.5 mV/600 Ohm (mic), 150 mV/47 kOhm (line), 1 mV/47 kOhm (phono) |
| Attenuation factor                       | : -   |
| Frequency range                          | : 80-15,000 Hz  |
| Crossover network                        | : -   |
| Crossover frequency                      | : -   |
| Integrated limiter                       | : -   |
| Equalizer bass                           | : $\pm 10$ dB/100 Hz  |
| Equalizer midrange                       | : -   |
| Equalizer treble                         | : $\pm 10$ dB/10 kHz  |
| S/N ratio                                | : $\geq 60$ dB (mic), $\geq 70$ dB (line)                           |
| Crosstalk attenuation                    | : -   |
| THD                                      | : $< 1\%$   |
| Mains voltage                            | : $\approx 230$ V   |
| Mains frequency                          | : 50 Hz   |
| Power consumption, operation             | : 280 VA  |
| Power consumption, standby               | : -   |
| Standby current                          | : -   |
| Operating voltage (possible alternative) | : DC 24 V   |
| Power supply (possible alternative)      | : DC 11 A   |
| Admiss. ambient temp.                    | : 0-40 °C   |

Width : 420 mm  
Height : 122 mm  
Depth : 350 mm





|                 |  |
|-----------------|--|
| Rack spaces, RS | : -  |
| Weight          | : 12.28 kg   |
| Connections     | : 1 x 6.3 mm jack (mic input), 3 x XLR, bal. (mic/line inputs), 1 x RCA L + R (line input), 1 x RCA L + R (phono/line input), 1 x twin spring-loaded terminal (telephone input), 1 x twin spring-loaded terminal (tuner output), 1 x twin spri |