

## SA-160BT - Amplifier



**Mini stereo amplifier, 2 x 30 W**, with Bluetooth interface, NFC and remote control.

- Integrated hi-fi audio amplifier
- For speakers with an impedance of 8 Ohm
- Volume control with integrated source selector function, LED indicator
- Near Field Communication (NFC)
- Gold-plated speaker terminals
- 1 stereo input via RCA jacks L/R
- 1 line output via 3.5 mm stereo jack
- Fixed antenna
- Metal housing
- Power is provided via enclosed power supply

## Tekniset tiedot:

|  |                    |
|--|--------------------|
| Peak output power                        | : 2 x 60 W         |
| Power rating                             | : 60 W             |
| Power rating at 2 Ohm                    | : -                |
| Power rating at 4 Ohm                    | : -                |
| Power rating at 8 Ohm                    | : 2 x 30 W         |
| Power rating at 16 Ohm                   | : -                |
| Power rating at 100 V                    | : -                |
| Power rating with 4 Ohm                  | : -                |
| bridged operation                        |                    |
| Power rating with 8 Ohm                  | : -                |
| bridged operation                        |                    |
| Output impedance                         | : -                |
| Channels                                 | : 2                |
| Zones                                    | : -                |
| Inputs                                   | : 660Â mV/10Â kOhm |
| Attenuation factor                       | : -                |
| Frequency range                          | : 20-20,000 Hz     |
| Crossover network                        | : -                |
| Crossover frequency                      | : -                |
| Integrated limiter                       | : -                |
| Equalizer bass                           | : -                |
| Equalizer midrange                       | : -                |
| Equalizer treble                         | : -                |
| S/N ratio                                | : ? 99 dBA         |
| Crosstalk attenuation                    | : -                |
| THD                                      | : -                |
| Mains voltage                            | : -                |
| Mains frequency                          | : -                |
| Power consumption, operation             | : -                |
| Power consumption, standby               | : -                |
| Standby current                          | : 100 mA           |
| Operating voltage (possible alternative) | : -                |
| Power supply (possible alternative)      | : -                |
| Admiss. ambient temp.                    | : 0-40 °C          |
| Width                                    | : 150 mm           |
| Height                                   | : 49 mm            |
| Depth                                    | : 122 mm           |



|                 |   |
|-----------------|---|
| Rack spaces, RS | : -   |
| Weight          | : 610 g   |
| Connections     | : 1 x RCA L/R (line), 4 x spring-load. speaker<br>term.(speakers) |