

SKYROCK - Mobile Outdoor Sound Box



Portable PA speaker system,

with integrated Bluetooth receiver The perfect solution for all your sound needs! Whether you're hosting a party, giving a presentation, or simply need to amplify your music, this system is designed to deliver exceptional performance and crystal-clear sound. With the option to operate via mains connection or using the optional rechargeable lead gel battery (12 V/18 Ah), you can take this speaker system wherever you go. At moderate volume, the battery can last up to 40 hours, while at full volume, it can last up to 10 hours. Integrated LED indicator shows the charging status. The Bluetooth receiver (version 5.0) allows for wireless connection of portable audio players, so you can easily stream your music from your phone, tablet, or laptop. The Bluetooth TWS feature (True Wireless Stereo) also lets you link two PA speaker systems SKYROCK to a stereo speaker system, providing an immersive sound experience. Featuring a high-performance class D version 120 W, this 2-way speaker system comes with a 38 cm (15") bass speaker and 25.4 mm (1") horn tweeter, delivering an outstanding sound quality, and an output up to 129 dB. This speaker system comes with one adjustable microphone input via comb. jack (XLR/6.3 mm) and one adjustable aux input (3.5 mm jack), providing flexibility for your needs. There is also a USB charging port for your portable audio players, ensuring you never run out of battery while on the go. Please note that this speaker system is supplied without a rechargeable lead gel battery, but a matching rechargeable battery WP18-12SHR is available as an option. Get ready to experience an exceptional sound quality with the SKYROCK.

Tekniset tiedot:

Rated power (P_{RMS})	: 55 W (bass) 21 W (tweeter)
Peak output power	: 130 W
Frequency range	: 38-20,000 Hz
Carrier frequency	: -
Operating range	: -
Inputs	: 12 mV/1 kOhm (mic), 70 mV/3 kOhm (aux)
Link	: -
THD	: -
Max. SPL	: 129 dB
Equalizer, bass	: -
Equalizer, midrange	: -
Equalizer, treble	: -
Power supply	: ∿ 100-240 V/50-60 Hz/120 VA, optional rech. batt. 12 V/18 Ah (WP18-12SHR)
Admiss. ambient temp.	: 0-40 °C
Dimensions	: 470 x 815 x 365 mm
Weight	: 23.4 kg
Connections	: 1 x XLR/6.3 mm jack (mic), 1 x 3.5 mm jack (aux) 1 x USB Type-A