

AKB-60 - Amplifier Module

60
W_{RMS}



Active speaker module, mono, 45 W at 4 Ohm

- Active module for activating passive speakers
- For mounting e.g. to the rear side of passive speakers
- Line input via XLR or RCA
- Adjustable master output
- Very well-suited as a measuring amplifier of acoustic analysers
- Fanless concept with large heat sink

Tekniset tiedot:

| | |
|--|--------------------------------------|
| Peak output power | : 60 W |
| Power rating | : 45 W |
| Power rating at 2 Ohm | : - |
| Power rating at 4 Ohm | : 45 W |
| Power rating at 8 Ohm | : 30 W |
| Power rating at 16 Ohm | : - |
| Power rating at 100 V | : - |
| Power rating with 4 Ohm | : - |
| bridged operation | |
| Power rating with 8 Ohm | : - |
| bridged operation | |
| Output impedance | : - |
| Channels | : 1 |
| Zones | : - |
| Inputs | : 0.4 V/20 kOhm bal., 11 kOhm unbal. |
| Attenuation factor | : - |
| Frequency range | : 15-50,000 Hz |
| Crossover network | : - |
| Crossover frequency | : - |
| Integrated limiter | : - |
| Equalizer bass | : - |
| Equalizer midrange | : - |
| Equalizer treble | : - |
| S/N ratio | : ? 80 dB |
| Crosstalk attenuation | : - |
| THD | : < 0.01% |
| Mains voltage | : ~ 230 V |
| Mains frequency | : 50 Hz |
| Power consumption, operation | : 90 VA |
| Power consumption, standby | : - |
| Standby current | : - |
| Operating voltage (possible alternative) | : - |
| Power supply (possible alternative) | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Width | : 212 mm |
| Height | : 52 mm |
| Depth | : 190 mm |



| | |
|-----------------|---|
| Rack spaces, RS | : - |
| Weight | : 2.2 kg |
| Connections | : 1 x XLR input, bal., 1 x RCA L/R (input), speaker cable for connecting 4-8Ω Ohmspeaker systems |