

PSS-3000E - Switching Power Supply, max 3A



Switch-mode power supply, 3 A max.,
high energy efficiency, complies with EU ecodesign directive.

- Saves electricity costs due to low power consumption in standby mode (< 0.3 W)
- Switchable output voltage
- Protected against short circuit, overload and overheating
- Power LED
- 1.8 m connection cable
- Selectable polarity by reversing the supplied adapters
- 7 plug-in adapters: plugs: 2.5 mm, 3.5 mm, hollow plugs: 2.35/0.75 mm, 3.5/1.35 mm, 5.0/2.1 mm, 5.5/2.1 mm, 5.5/2.5 mm

Tekniset tiedot:

| | |
|-----------------------------|---------------------------------------|
| Category | : switch-mode power supply |
| Input voltage | : \approx 100-240 V/50-60 Hz/800 mA |
| Output voltage | : DC 5/6/7.5/9/12/13.5/15 V |
| Charging/output current | : 3/3/3/3/2.4/2.4 A, 36 VA |
| Charging time | : - |
| Trickle charge | : - |
| Polarity selection | : yes |
| Switchable output voltage | : yes |
| Reactivation | : - |
| Connections | : plug-in adapter |
| Cable length | : 1.8 m |
| Short-circuit protection | : yes |
| Overload protection | : yes |
| Overheat protection | : yes |
| Reverse polarity protection | : - |
| Detection of faulty battery | : - |
| Protective class | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Dimensions | : 50 x 32 x 115 mm |
| Weight | : 300 g |
| Position | : - |
| Other features | : - |